

SCREW EXTRUDER

STANDARDS: BS 598:107, 1377:4, 1924:2, ASTM D698, D1587, D1883

The unit extrudes samples from Ø35 to 101,6 mm with maximum stroke of 650 mm.

Horizontal Type and 60 kN extrusion force.

There are two models as Hand operated and Motorised.

Supplied complete with adaptors (ring and tamper) to extrude samples having Ø 38 mm and Ø 100 mm, supporting bench, sample receiving table both adjustable in height and lowerable.

Technical Specifications:

Product Code	HR-S6320	HR-S6330
Product Name	Hand Operated Screw Extruder	Motorised Screw Extruder
Stroke (mm)	650	650
Dimensions (cm)	70x170x120	70x170x130
Weight (kg)	65	120
Power Supply	---	220 V, 50 Hz, 1 ph

Spare Parts & Accessories:

Product Code	Product Name
HR-S6320/1	Adaptor for Ø 38 mm moulds
HR-S6320/2	Adaptor for Ø 50 mm moulds
HR-S6320/3	Adaptor for Ø 70 mm moulds
HR-S6320/4	Adaptor for Ø 100 mm moulds
HR-S6320/5	Adaptor for Ø 150 mm moulds



38 MM HAND OPERATED HYDRAULIC SAMPLE EXTRUDER

STANDARDS: BS 1377-1

38 mm Hand Operated Hydraulic Sample Extruder with Trimming Knife, 38mm Split Former & Cutting Tool comprises a vertically mounted lever action hydraulic jack, with the body extended to form a chamber which accommodates a 38 mm diameter sample tube.

Supplied complete with Trimming Knife, 38mm Split Former, Wire Saw and 12 pieces Wire.

Technical Specifications:

Product Code	Product Name
HR-S6340	38 mm Hand Operated Hydraulic Sample Extruder

Spare Parts & Accessories:

Product Code	Product Name
HR-S6340/1	38mm Split Former
HR-G0755	Trimming Knife
HR-G0753	Open Wire Saw
HR-G0754	Wire. Pack of 12

